

## Boston Concord Air



**Tube:** Nitrile

**Reinforcement:** Fiber, 2 Braid or 2 Ply

**Cover:** Neoprene 1/2', 3/4' & 1' Pinpricked  
Vinyl Nitrile 1-1/4', 1-1/2', 2' & 3' Pinpricked

**Color:** Red

**Temperature Range:** -40°F To +200°F

**Type Of Branding:** Impression

**Working Pressure:** 300-400 PSI

**Type Of Coupling:** 'U' Series or 430 'U' Series, Interlocking, Non-Reattachable (Swaged), Quick Acting, Long Shank, Steel Nipple. Clamps —Interlocking or Bands.

### Features:

- Neoprene cover
- Nitrile tube
- Continuous permanent brand
- Two textile braids or ply

### Advantages:

- Abrasion, oil, and weather resistant
- Good oil resistance
- Easy identification
- Easy to handle
- Kink resistant

### Markets:

- Construction Industry
- Forest Industry
- Metal Working
- Mining

### Applications:

- Provide power to air-operated construction equipment
- Transfer air and water
- Power air-operated drills, boring, and mining equipment

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	REINFORCEMENT	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	MTO* MIN. ORDER QTY.	STANDARD LENGTH (FT)
H600208	1/2	12.7	2 Br	29/32	23.0	31	400	—	50
H600208-100									100
H600208-150									150
H600212	3/4	19.1	2 Br	1-3/16	30.2	46	400	—	50
H600212-100									100
H600212-150									150
H600216	1	25.4	2 Br	1-1/2	38.1	67	400	—	50
H600216-100									100
H600216-150									150
H600220	1-1/4	31.8	2 Ply	1-13/16	46.0	86	400	—	50
H600220-100									100
H600220-150									150
H600224	1-1/2	38.1	2 Ply	2-1/16	52.4	99	400	—	50
H600224-100									100
H600224-150									150
H600232	2	50.8	2 Ply	2-5/8	66.7	127	300	—	50
H600232-100									100
H600232-150									150
H600248	3	76.2	2 Ply	3-9/16	90.49	192	200	600	50
H600248-100									100
H600248-150									150

\*MTO—Made To Order