

 Refer to warnings and safety information on pages 3-4 and pages 115-118

**Boston Concord 250**



**Tube:** EPDM  
**Reinforcement:** Wire, 2 Braid  
**Cover:** EPDM/Pinpricked  
**Color:** Black (BK), Available in Red (RD)  
**Temperature Range:** +450°F  
**Type Of Branding:** Ink Print  
**Working Pressure:** 250 PSI (Depending on coupling)  
 10:1 Safety Factor  
**Type Of Coupling:** Boston Wolf Permanent Crimp Couplings or Interlocking.  
 Clamps—Interlocking, (2 Bolt, 4 Bolt).

**Features:**

- EPDM cover
- EPDM tube
- Continuous ink print and date code
- Minimum 10-to-1 safety factor
- Available with red cover (made-to-order)
- Date code

**Advantages:**

- Heat, age, ozone and weather resistant.
- Excellent heat resistance
- Handles most steam cleaning detergents
- Easy identification
- Meets safety standards of RMA
- Color coding
- Safety & maintenance records

**Markets:**

- Chemical/Petroleum Industry
- Industrial Cleaning Markets
- Ship Building
- Food Industry
- Lumber/Woodworking
- Plywood Mfg./Cardboard
- Pulp Processing

**Applications:**

- Transfer of steam for processing products and cleaning equipment
- Transfer of steam or hot 200°F detergent-type solutions for cleaning of equipment, tanks, buildings, etc.
- Transfer of steam to melt glues, waxes, etc.

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT	MAXIMUM WORKING PRESS. (PSI)	STANDARD LENGTH (FT)
H956808	1/2	12.7	2	1-1/32	26.2	46	250	50(BK,RD)
H956812	3/4	19.1	2	1-11/32	34.1	70	250	50(BK,RD)
H956816	1	25.4	2	1-9/16	39.7	96	250	50(BK,RD)

*Not to be used as a pressure washer hose*